

## DCM Dispersion Compensator card



### Product overview

DCM dispersion compensator has the function of slope compensation. It can compensate the dispersion slope of the standard single mode fiber (G.652) in the C band, which can optimize the residual dispersion. It is based on the mature and reliable optical fiber technology, which can improve the performance of the optical transmission system. The dispersion of the 1550nm wavelength can reach -10 to -2100ps/nm, and can provide products with special requirements for central wavelength and dispersion.

### Product features

- G.652 fiber C band 100% slope compensation ( Standard value )
- Low insertion loss
- Low polarization mode dispersion
- Wide band dispersion compensation for DWDM system
- Performance index through the GR-2854-CORE telcordia standard certification
- Reliability through the GR-2854-CORE telcordia standard certification

### Performance index

P/N	Compensation Distance(km)	Dispersion (ps/nm)	Insertion Loss (dB)	PMD (ps)	PDL (dB)
DCM	10	-170±3%	≤2.5	≤0.5	≤0.1
DCM	20	-340±3%	≤2.8	≤0.6	≤0.1
DCM	30	-510±3%	≤3.6	≤0.7	≤0.1
DCM	40	-680±3%	≤4.2	≤0.8	≤0.1
DCM	50	-850±3%	≤4.5	≤0.9	≤0.1
DCM	60	-1020±3%	≤4.8	≤1.0	≤0.1
DCM	70	-1190±3%	≤5.3	≤1.1	≤0.1
DCM	80	-1360±3%	≤5.8	≤1.2	≤0.1
DCM	90	-1530±3%	≤6.2	≤1.3	≤0.1
DCM	100	-1700±3%	≤6.5	≤1.4	≤0.1